

MB Bulkhead Series

Technical Data

The MB Bulkhead connector is designed to enable precise and accurate connection of tubes is required, without the need for a detachable plug and socket.

Fittings:	Legris carstick as standard (others available)
Body material:	Black Acetal (others available)
Maximum pressure:	10 bar
Vacuum capacity:	Reduced pressure to 755 mm .hg
Temperature range:	-40°C to 80°C
Panel thickness:	1.5mm to 5.0mm
Working medium:	Compressed air (for others please consult sales)
Place of origin:	All manufactured in the UK
Tube sizes:	4mm, 6mm, 8mm, 10mm and 12mm metric. 1/4" and 3/8" imperial
Dimensions:	Drawings available on product page

Stock Configurations

Part Number	Tube Size	Number of Ways	Body Size
MB040240	4mm	2	40mm
MB040450	4mm	4	50mm
MB040650	4mm	6	50mm
MB040750	4mm	7	50mm
MB040870	4mm	8	70mm
MB041070	4mm	10	70mm
MB041270	4mm	12	70mm
MB041675	4mm	16	75mm
MB060240	6mm	2	40mm
MB060450	6mm	4	50mm
MB060650	6mm	6	50mm
MB060750	6mm	7	50mm
MB080250	8mm	2	50mm
MB080450	8mm	4	50mm
MB080670	8mm	6	70mm
MB080870	8mm	8	70mm

Need a quote?

If you need a quote for one of our stock configuration units, please specify the part number and quantity require. However, please remember over 50% of our manufacturing is bespoke items, so if you have a requirement that is not listed above, do not hesitate to contact the sales office on 0044 (0) 1636 679415 or sales@pneutherm.com

The more information you can give us about your application, the better product we can supply.